ALCHIMICA S.A.

7, Lampsakou Str. 11528 Athens GREECE.

Tel: +30 214 4167 700 Fax: +30 214 4167 701





EU-Declaration of Performance

In accordance with Annex III of Regulation (EU) No.305/2011 and Commission Delegated Regulation (EU) No 574/2014

No. 2884-CPR-00157_XPS_TH

1. Unique identification code of the product-type:

HYGROSMART COVER OVER SYSTEM (XPS_TH)

2. Intended use:

External Thermal Insulation Composite Systems (ETICS) with renderings

3. Manufacturer:

ALCHIMICA SA 7, Lampsakou Str., 11528 Athens-Greece

4. Systems of AVCP:

System 2+

5. European Assessment Document:

EAD 040083-00-0404

European Technical Assessment:

ETA-20/0642 of 09-08-2021

Technical Assessment Body:

Technical and Test Institute for Construction Prague (1020)

Notified body:

Business Quality Verification (2884)

ALCHIMICA S.A.

7, Lampsakou Str. 11528 Athens GREECE.

Tel: +30 214 4167 700 Fax: +30 214 4167 701



6. Declared performance

Essential characteristics	Performance	Harmonized technical specification
Reaction to fire of thermal insulation material	E	
Water absorption	After 1h: 0.03 kg/m² After 24h: 0.19 kg/m² (Base coat)	
	After 1h: 0.02 kg/m ² After 24h: 0.03 kg/m ² (Complete rendering)	
Hygrothermal behaviour	Resistant to hygrothermal cycles	-
Freeze / thaw behaviour	Freeze / thaw resistant	-
Impact resistance	Impact Resistance category III	EAD 040083-00- 0404
Bond Strength	Between the base coat and the thermal insulation product (mortar or paste): Initial state: ≥ 0.168 MPa After hygrothermal cycles: ≥ 0.28MPa Between the adhesive and the substrate: Initial state: ≥ 1.24 MPa Immersion 48h and 2h drying: ≥1.18MPa Immersion 48h and 7d drying: ≥1.56MPa Between the adhesive and the thermal insulation product: Initial state: ≥ 0.12MPa Immersion 48h and 2h drying: ≥ 0.10MPa	
Thermal resistance	Immersion 48h and 7d drying: \geq 0.16MPa \geq 1.00 [(m ² *K)/W]	_

7. Appropriate Technical Documentation and/or Specific Technical Documentation:

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by: Krimizis Christos CEO

Athens 14/04/2022